



Subscape 10 PRODUCT SPECIFICATIONS

System Type	10" In-Ground Bandpass Subwoofer (250 W transformer for 70.7 V or transformer bypass applications)
Impedance (Nominal) ¹	8 ohm
Sensitivity dB @ 2.83 V / 1 M	87 dB
Sensitivity dB @ 1 W / 1 M ²	87 dB
Frequency Response (±3 dB) ³	32 Hz - 105 Hz
Frequency Response (±10 dB) ³	25 Hz - 150 Hz
Max. Program Power ⁴	500 W
Max. Continuous Power RMS ⁵	250 W
Max. SPL dB @ 1 M ⁶	111 dB
Tap Selector	Wire leads
Transducer: Low-Frequency Driver	10" Polypropylene Cone w/ Butyl Rubber Surround
Low-Frequency Voice Coil	2.0 in / 50.8 mm
Crossover Frequency	90 Hz
Network Type: Low Pass	12 dB per octave, 2nd order
Network Type: High Pass	N/A
Enclosure Material	Rotomolded ABS plastic
Grille	Brown vent cap
Inputs	Wire leads
Colors	Brown
Length	27 in / 685.8 mm
Width	12 in / 304.8 mm
Height	25 in / 635 mm
Weight	33.55 lbs / 15.22 kg
Packaging	One per box
Included Accessories	Wire Nuts
Optional Accessories	Brown Top Rock (TOP ROCK MD - B) Grey Top Rock (TOP ROCK MD - G) Sandstone Top Rock (TOP ROCK MD - S)
Certifications	CE, RoHS

Description

The Rockustics Subscape 10 from SoundTube is a direct-burial, 10" subwoofer to complement Periscape speakers. With 250 watts (RMS) of power handling, it brings strong bass response to your outdoor installations and is the perfect companion to Periscape spike-mount speakers. Once installed, the only visible part of the speaker is a discreet, brown vent cap. One Subscape subwoofer is suitable for installations of up to 7 Periscape units; additional subwoofers are recommended for larger installations. The Subscape 10 may also be used with other SoundTube Rockustics series speakers or other outdoor products. A built-in transformer provides convenience for 70.7V installations; the subwoofer may also be operated in 8 ohm direct mode. We recommend pairing Subscape subwoofers with the SoundTube MCA2004t amplifier for both low-impedance and 70.7V installations, or the PhaseTech P350 subwoofer amplifier (low-impedance only).

Features

- One 10" (254 mm) polypropylene cone with a butyl rubber surround attached to a reinforced baffle.
- High output (111 dB) and maximum efficiency with strong bass response to maximize listener's low-frequency experience
- 250 W, low insertion-loss transformer with external wire leads for 70.7 V and 8-ohm transformer-bypass configurations.
- High-quality rotomolded enclosure
- Included accessories: Wire nuts
- Optional accessory: Brown, Grey, or Sandstone Top Rock (TOP ROCK MD)

¹ Impedance listed per IEC 60268-5 with a minimum less than 80% the nominal impedance

² 1 W/1 M sensitivity determined using nominal impedance

³ Frequency response measured in half or full space as dictated by speaker mounting configuration

⁴ Max program power is 3 dB above max continuous power

⁵ Continuous power rating, EIA-426-B test

⁶ Max output based on max continuous power

SoundTube®

13720 W. 109th St.
Lenexa, KS 66215
Phone: 913.663.5600
Fax: 913.663.3200
Toll Free: 855.663.5600
www.soundtube.com

