

S C M I O O S E : 3 - w a y a c t i v e / p a s s i v e

F e a t u r e s

n
n
n
n
n
n
n

- New ATC designed and built 25mm Soft Dome tweeter model SH25-76S.
- The Unique ATC 75mm Soft Dome midrange model SM75-150S.
- The latest 314mm short coil super linear magnet Bass Driver model SB75-314SL.
- Fully discrete amplifier for each drive unit combined to create a Tri-amplifier of 350 watts with active crossover filters, phase correction and overload protection.
- Accurate timbre, wide dispersion and perfect imaging.
- Any veneer to order.
- Choice of top brow finish and colour detail.
- 6 year warranty.

S p e c i f i c a t i o n s

- Drivers :** HF 25mm, Mid ATC 75mm Soft Dome, LF 314mm SL
- Frequency Response (-2dB) :** 65Hz-17kHz
- Frequency Response (-6dB) :** 32Hz-25kHz
- Matched Response :** +/- 0.5dB
- Dispersion :** ±80° Coherent Horizontal, ±10° Coherent Vertical
- Max SPL :** 115dB
- Crossover Frequencies :** 380Hz and 3.5KHz
- Connectors :** Male XLR
- Filters :** All active
- Amplifier Output :** 200w LF, 100w Mid, 50w HF
- Loudspeaker Dimensions (HxWxD) :** 1150 x 419 x 585mm
- Weight :** 79kg

Passive version

- Sensitivity :** 88db@1watt@1 metre
- Loudspeaker Dimensions (HxWxD) :** 1150 x 419 x 592mm
- Weight :** 74kg **Suitable Amps :** 100-1500watts

ATC reserves the right to vary products and specifications without prior notice.

