

S C M I 5 0 S E : 3 - w a y a c t i v e / p a s s i v e

Features

New ATC designed and built 25mm Soft Dome tweeter model SH25-76S.

The unique ATC 75mm Soft Dome midrange model SM75-150S.

The latest 375mm short coil super linear magnet Bass Driver model SB75-375SL.

Fully discrete amplifier for each drive unit combined to create a Tri-amplifier of 350 watts with active crossover filters, phase correction and overload protection.

Accurate timbre, wide dispersion and perfect imaging.

Any veneer to order.

Choice of top brow finish and colour detail.

6 year warranty.



Specifications

Drivers : HF 25mm, Mid ATC 75mm Soft Dome, LF 375mm SL

Frequency Response (-2dB) : 60Hz-17kHz

Frequency Response (-6dB) : 25Hz-25kHz

Matched Response : +/- 0.5dB

Dispersion : ±80° Coherent Horizontal, ±10° Coherent Vertical

Max SPL : 117dB

Crossover Frequencies : 380Hz & 3.5kHz

Connectors : Male XLR

Filters : All active

Amplifier Output : 200w LF, 100w Mid, 50w HF

Loudspeaker Dimensions (HxWxD) : 1205 x 533 x 634mm

Weight : 97kg

Passive version

Sensitivity : 91db@1watt@1 metre

Loudspeaker Dimensions (HxWxD) : 1205 x 533 x 640mm

Weight : 93kg **Suitable Amps :** 100-1500w

ATC reserves the right to vary products and specifications without prior notice.