



www.denonpro.com

PHONE: [401] 658.3131

December 18, 2023



DN-300RMKII Solid-State SD/USB Audio Recorder

Key Features:

- Records WAV and Mp3 files to SD and USB media simultaneously
- Simple and easy to use
- Powers-up in record-ready mode
- Dual Stereo & Dual Mono modes for recording -10dB safety tracks on the same media
- Balanced and unbalanced inputs and outputs
- Compact 1RU design

Overview:

The DN-300RMKII records to both SD and USB media simultaneously – perfect for recording conferences where the client needs a copy of the recording after the event. With outstanding ease-of-use and simple operation, anyone can use the DN-300RMKII right out of the box and record to SD, USB or both. Utilizing Dual Mono or Dual Stereo modes, the ability to record a second mono or stereo file at -10dB on the same media is supported - even when recording to both SD and USB at the same time. The DN-300RMKII is exactly what the market is looking for in terms of a simple but high-quality recording solution for commercial applications. The DN-300RMKII gives installers and contractors the flexibility and convenience they need for total commercial recording capability.

Specifications:

- Digital Audio System
 - System:
 - Solid-state SD/USB audio recorder/player
 - Compatible Media (FAT16, FAT32)
 - USB Device (mass storage class)
 - SD/SDHC
 - SDXC
 - Supported File Formats
 - MP3
 - Sampling frequency:
 - 44.1 kHz
 - Bit rate:
 - 192, 256 kbps (recording); 64 - 320 kbps and VBR (playback)
 - Format:
 - MPEG1 Audio Layer 3
 - File extension:
 - .mp3
 - WAV
 - Sampling frequency:
 - 44.1, 48 kHz
 - Bit depth:
 - 16-bit (44.1 kHz), 24-bit (48 kHz)
 - Format:
 - Waveform Audio File Format
 - File extension:
 - .wav
 - Number of Channels:
 - 2 channels / stereo
 - Audio Frequency Range:
 - 10 - 20 kHz (\pm 1.0dB recording, \pm 0.8 dB playback)
 - Signal-to-Noise Ratio

- Recording:
 - > 95 dB (1 kHz, 0dB A-weighted)
- Playback:
 - > 95 dB (1 kHz, 0dB A-weighted)
- Channel Separation
 - Recording:
 - > 80 dB (1 kHz, 0dB A-weighted)
 - Playback:
 - > 90 dB (1 kHz, 0dB A-weighted)
- Wow and Flutter:
 - < 0.001 %
- Distortion
 - Recording:
 - < 0.008 %
 - Playback:
 - < 0.006 %
- Total Harmonic Distortion:
 - < 0.01% (1 kHz, 0dB A-weighted)
- Inputs
 - Balanced XLR
 - Nominal level:
 - +4 dBu ± 1 dBu
 - Minimum level:
 - - 40 dBu
 - Maximum level:
 - 20 dBu ± 1 dBu
 - Input impedance:
 - 18 k Ω
- Outputs
 - Balanced XLR
 - Nominal level:
 - +4dBu ± 1 dBu
 - Maximum output level:
 - +20 dBu ± 1 dBu
 - Output impedance:
 - 600 Ω ± 10%
 - Unbalanced RCA
 - Nominal level:
 - -10 dBV ± 2 dBV
 - Minimum output level:
 - 6 dBV ± 2 dBV
- Connectors
 - (2) XLR outputs
 - (1) 1/4" (6.35mm) headphone output
 - (1) RCA stereo output pair
 - (2) XLR inputs
 - (1) RCA stereo input pair
 - (1) USB port
 - (1) SD card slot
 - (1) IEC AC power input
- Power
 - Connection:
 - IEC
 - Input Voltage:
 - 100 - 240 V~, 50/60 Hz
- Dimensions (width x depth x height):
 - 19.0" x 10.92" x 1.72" (484 x 277 x 44mm)
- Weight:
 - 6.6 lbs (3 kg)