



Features

- 1 Power Button with LED
- 2 Reboot Button
- 3 Voltage / Current Button
- 4 Dimmer Button
- 5 Voltage / Current Display
- 6 Status Indicators
- 7 Front AC outlet
- 8 Front Outlet Status
- 9 2 Front USB-A Ports
- 10 2 Rear USB-A Ports
- 11 8 Rear AC Outlets
- 12 8 ft Power Cord with 360° Rotating Plug

Technical Specifications

Number of Outlets:	9 - AC Outlets (8 rear, 1 front)
Number of USB Outlets:	4 USB-A Ports - 5V / 2.4 A each pair (2 Rear , 2 front)
Number of Isolated Groups:	3 (Group 1 outlets are high current)
AC Power Cord:	8 ft with 360° rotating NEMA 5-15P plug
AC Outlet:	all 9 filtered with surge protection
Protection Modes:	Surge, Under / Over Voltage Shutdown
Thermal Fusing:	Yes
Maximum Current:	15 Amps
Line Voltage:	120V AC @ 60Hz
Max Spike Voltage / Current:	6,000V / 165,000A
Max Energy Dissipation:	3240 Joules
Response Time:	<1 nanosecond
Filtration:	EMI / RFI up to 70dB
App Control:	ELAC ProTek app (free download)
App Capabilities:	Group Controlled Outlet, scheduling and timers
Bluetooth:	BLE (Bluetooth Low Energy) 2.4 GHz