

	DB53	DB63	DF53	DF63	DC53	DC63	DA43
SPEAKER TYPE	2-WAY, BASS REFLEX		3-WAY, BASS REFLEX		2-WAY, SEALED		
FREQUENCY RESPONSE	42 TO 38KHZ	42 TO 38KHZ	38 TO 38KHZ	31 TO 38KHZ	57 TO 38KHZ	50 TO 38KHZ	48 TO 38KHZ
NOMINAL IMPEDANCE	6 Ω	6 Ω	4 Ω	4 Ω	6 Ω	6 Ω	6 Ω
MINIMUM IMPEDANCE	4.8 Ω at 200 Hz	4.8 Ω at 200 Hz	4.2 Ω at 550 Hz	3.6 Ω at 500 Hz	4.8 Ω at 200 Hz	4.8 Ω at 200 Hz	5.0 Ω at 200 Hz
SENSITIVITY @2.83 V/1M	86.5 dB	87 dB	87.5 dB	87.5 dB	87.5 dB	87.5 dB	84 dB
CROSSOVER FREQUENCY	1900 Hz	2000 Hz	500 Hz, 2100 Hz	550 Hz, 2000 Hz	1900 Hz	2000 Hz	2400 Hz
RECOMMENDED AMPLIFIER POWER	20 - 120 W	20 - 140 W	30 - 150 W	30 - 180 W	30 - 120 W	30 - 140 W	20 - 80 W
NOMINAL/PEAK POWER HANDLING	120 W	120 W	140 W	140 W	120 W	120 W	80 W
TWEETER	1 - INCH ALUMINUM DOME						
MIDRANGE (ARAMID-FIBER)	-	-	2 x 5 ¼ "	2 x 6 ½ "	-	-	-
WOOFER (ARAMID-FIBER)	5 ¼ "	6 ½ "	5 ¼ "	6 ½ "	2 x 5 ¼ "	2 x 6 ½ "	4.0 "
CABINET	CARB2 RATED 16MM MDF						
CABINET FINISH	BLACK ASH VINYL, SATIN BLACK VINYL FRONT						
PORT	DUAL FLARED				SEALED		
BINDING POST	5-WAY METAL						
WIDTH (IN / MM)	6.8/172	7.7/195	6.8/172	7.7/195	19.0/482	21.0/533	6.8/172
HEIGHT (IN / MM)	12.2/311	13.3/339	40.6/1030	43.1/1094	6.8/172	7.7/195	6.7/170
DEPTH (IN / MM)	10.5/267	11.7/298	9.7/246	10.6/268	9.2/234	11.7/298	9.7/246
Net Weight (lbs / KG)	13.34/6.05	17.3/7.85	34.6/15.7	38.8/17.6	19.2/8.7	23.6/10.7	7.3/3.3

