

## FRONT and BACK PANEL FEATURES



## SPECIFICATIONS

### AC Input Voltage

120/240V single phase, or 120/208V three phase.  
 Input Current: 120 Amps maximum  
 Output: Six, 120V 20A circuits

### Maximum AC Current Rating

Six, 120V 20A circuits for 120A total.

### Power Distribution Block

Wire Gauge 2, 3, 4-6 AWG,  
 Phase indicators: 3 LEDs, one per phase X, Y, and Z

### AC Output Receptacles

Rear Panel Outlets: 6 duplex NEMA 5-20R sequenced.  
 Front Panel: 6 thermal circuit breakers, one per duplex pair.

### Operating Temperature and Humidity

5 to 40C (40 to 105F), <90% Relative Humidity

### User Interface

Key-switch: Front panel, 3 position (On/Off/Remote)  
 Keys: Included, 1 pair  
 Push Button Switch: Front panel  
 Circuit Breakers: Front panel, push-button; 6, 20A Thermal Breakers  
 Output Circuit Status: Front panel indicators – one per output  
 Configuration Switches: Front panel, hidden by security cover;  
 3 maximum delay switches – 1, 2, and 4 minute  
 Force Off NO/NC, 12V mode On/Off, GND mode ON,  
 Momentary/Maintained mode selection  
 Fine Delay Adjustment: Potentiometer hidden by security cover.  
 Sequence Bypass : 6 Switches, 3 States (ON/SEQUENCE/OFF)  
 Phase indicators: 3 LEDs, one per phase X, Y, and Z



### Control/Status/Triggering (Rear Panel)

Remote Terminal: Phoenix-type 4 Pin Connector w/Screw Terminals;  
 +12V @ 250mA, STAT, REM, GND (Class 2 wiring)  
 +5 to 30VDC at REM input terminal.  
 Delay Outputs: Phoenix-type 8-Pin Connector with Screw Terminals  
 6 relay contacts with NO and NC common connections (Class 2 wiring)  
 A, B, C, D, E, and F relay contacts switched with output circuits, 1A@48VDC  
 Force Off: Phoenix-type 2 Pin Connector with Screw Terminals;  
 Optically isolated, 12V, 10mA current source (Class 2 wiring)  
 Senses external relay contact closure

### Power Consumption

Standby: 5 Watts  
 Sequenced ON: 20 Watts

### Safety Agency

NTRL-C, RoHS Compliant

Specifications are subject to change without notice due to design improvements and upgrades.

### WEIGHTS, DIMENSIONS AND UPC CODES

MODEL	PRODUCT DIMENSIONS	WEIGHT	CARTON DIMENSIONS	WEIGHT	SINGLE UNIT UPC	MASTER PACK QTY	MASTER PACK UPC
ASD-120 2.0	19" L x 10" D x 3.5" H	16 lbs.	22"L x 18.5"D x 8"H	18 lbs.	654061041191	2	50654061041196

**FURMAN** [www.furmansound.com](http://www.furmansound.com)

Furman 1800 S. McDowell Blvd., Petaluma, CA 94954

©2016 Core Brands, LLC. All rights reserved.

Furman is registered trademark of Core Brands LLC, a Nortek Company.