

## Accessories and Lenses

<b>Supplied Accessories</b>	Remote control, power cord, computer cable, AA batteries x2, lens cover, adapter cover, security label, user's manual CD, user's manual, application CD
<b>Optional Accessories</b>	Wireless adapter (USBWL11N), HAS-9110 bracket, HAS-204L standard adapter, HAS-304H long adapter, wired remote HL03131
<b>Replacement Parts</b>	
<b>Lamp</b>	DT01931
<b>Remote Control</b>	HL03037
<b>Filter</b>	UX41161

## Projection Throw Chart (In inches)

Screen Size 16:10		Throw Distance	
Diagonal	Width	Min	Max
30	25	32	54
60	51	69	113
80	68	93	152
100	85	117	191
200	170	237	385
300	254	358	580

Throw Ratio: 1.4 - 2.3 :1 (distance : width)

## Specifications

<b>Display</b>	<b>Projection Technology</b>	3LCD, 3 chip technology
	<b>Resolution</b>	WXGA 1280 x 800
	<b>White Light Output</b>	5,000 ANSI lumens
	<b>Color Light Output</b>	5,000 ANSI lumens
	<b>Colors</b>	16.7 million colors
	<b>Aspect Ratio</b>	Native 16:10 / 4:3, 14:9 and 16:9 compatible
	<b>Contrast Ratio</b>	10000 : 1 (using active IRIS)
<b>Lens &amp; Operation</b>	<b>Throw Ratio</b> (distance : width)	1.4 - 2.3 : 1
	<b>Focus Distance</b>	32" - 580"
	<b>Display Size</b>	30" - 300"
	<b>Lens</b>	F = 1.65 - 2.15, x 1.6 manual zoom, focus & lens shift
	<b>Lamp Wattage</b>	300W
	<b>Expected Lamp Life*</b>	Approximately 4,000 hours (standard mode) 6,000 hours (Eco mode)
	<b>Expected Filter Life**</b>	Approximately 10,000 hours
<b>Compatibility</b>	<b>Speaker Output</b>	16W
	<b>Keystone</b>	H and V: +/- 30°
	<b>Computer</b>	VGA, SVGA, XGA, WXGA, WXGA+/SXGA/SXGA+/WSXGA+/UXGA/WUXGA, MAC 16"
	<b>H-Sync</b>	15 kHz - 106 kHz
	<b>V-Sync</b>	50 Hz - 120 Hz
	<b>Composite Video</b>	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM
	<b>Component Video</b>	480i, 480p, 576i, 720p, 1080i, 1080p
<b>Connectors</b>	<b>HDMI</b>	480i, 480p, 576i, 720p, 1080i, 1080p, Computer signal TMDS clock 27 MHz - 150 MHz
	<b>Digital Input</b>	HDMI x 2, HDBaseT x 1
	<b>HDMI Output</b>	HDMI x 1
	<b>Computer Input</b>	15-pin mini D-sub x 1
	<b>Computer Monitor Output</b>	15-pin mini D-sub x 1
	<b>Video Input</b>	
	S-Video	N/A
	Composite Video	RCA jack x 1
	Component Video	15-pin mini D-sub x 1 (shared with computer In 1)
	<b>Audio Input</b>	3.5 mm stereo mini jack x 1, RCA jack (L/R) x 1
	<b>Audio Output</b>	3.5 mm stereo mini jack x 1
	<b>Network LAN Wired</b>	RJ-45 port (10 base-T / 100 base-TX)
	<b>Network LAN Wireless</b>	USB-A, IEEE802.11 b/g/n - optional wireless adapter required
	<b>HDBaseT</b>	RJ-45 port x 1
	<b>USB</b>	Type A x 1 (wireless network)
	<b>Control Terminals</b>	9-pin D-sub x 1 (RS-232 control)
	<b>Ratings &amp; Warranty</b>	<b>Power Supply</b>
<b>Power Consumption</b>		440W / 420W
<b>Operating Temperature</b>		32°F - 95°F (0°C-35°C) (Standard) 32°F - 104°F (0°C-40°C) (Eco Mode)
<b>Dimensions (W x D x H)</b>		18.1" x 13.1" x 5.4" (excluding protruding parts)
<b>Weight</b>		Approximately 14 lbs.
<b>Approvals</b>		UL 60950-1 / cUL FCC Part 15 subpart B class A
<b>Warranty</b>	3 year limited parts and labor Extended Service Contract available (additional cost)	

\* Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

\*\* Actual filter life will vary by individual filter and based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.

# CP-WX5505

HI0448-02/16-Rev.2

All specifications subject to change without notice.

3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.

iPad and iPhone are registered trademarks of Apple Inc., registered in the U.S. and other countries.

©2016 Hitachi America, Ltd. All Rights Reserved.

**Hitachi America, Ltd.**

Toll Free: 1.800.HITACHI • Email: [dmd.info@hal.hitachi.com](mailto:dmd.info@hal.hitachi.com)

Web: [hitachi-america.us/projectors](http://hitachi-america.us/projectors)

Blog: [dmd.hitachi-america.us/blog](http://dmd.hitachi-america.us/blog)

