



Specification

Product	Q Active 200	Q Active 400	Hub
Acoustics			
Enclosure type	Reflex (ported)	Reflex (ported)	-
Full range driver	2 x BMR 58mm (2.25in)	2 x BMR 58mm (2.25in)	-
Subwoofer (high excursion)	1 x 114mm (4.5in)	2 x 114mm (4.5in)	-
Crossover frequency	150Hz	TBC	-
System frequency response (free boundary)	46Hz to 20kHz (-6dB)	TBC	-
Power (per speaker)			
Continuous power	100W	TBC	-
Peak power	280W	TBC	-
Power requirement			
Voltage range	100 - 240 VAC, 50/60 Hz	100 - 240 VAC, 50/60Hz	100 - 240 VAC, 50/60Hz
Weight and dimensions			
Un-boxed weight (per speaker)	7.5kg	17.5kg	0.5kg
Dimensions (per speaker) H x W x D	284 x 170 x 290mm (11.2 x 6.7 x 11.4in)	825 x 320 x 290mm (32.5 x 12.6 x 11.4in)incl. spikes & stabiliser	40 x 180 x 112mm (1.6 x 7.1 x 4.4in)
Dimensions on stand H x W x D	922 x 286 x 338mm (36.3 x 11.3 x 13.3in)	-	-
Wireless connectivity			
<i>Bluetooth</i>	-	-	v4.1 Low Energy
Wi-Fi	-	-	IEEE 802.11 a/b/g/n and 802.11ac compliant
Hi-Res Wireless Link frequency	5.8GHz	5.8GHz	5.8GHz
Remote control	-	-	2.4GHz
Audio playback			
Codec formats	-	-	AAC, WAV, FLAC, MP3, Vorbis, WMA & ALAC
Sample frequency	96kHz	96kHz	8 – 192kHz (depending on codec)
Bit depth	24bits	24bits	8 – 32bits (depending on codec)
Wired connectivity			
Digital optical	-	-	96kHz/24bit Toslink
Digital HDMI	-	-	96kHz/16bit ARC (2 channel)
Analogue (set to line level)	-	-	300mV/18kΩ
Analogue (set to phono MM)	-	-	2.6mV/47kΩ (RIAA Equalised)
Subwoofer output	-	-	1.20V (0-300Hz)