





## FEATURES & BENEFITS

- Double high current on demand
- Balanced AC surge protection
- · Resettable circuit breaker
- Rack mountable
- Compatible with UL1449 3rd edition for Type 3 locations
- Orange or blue Illuminated front rear switch

## **APPLICATIONS**

- · High end two channel
- Demanding home theaters
- For crisp and flawless AV experience

PARALLEL POWER DELIVERY FOR LOAD IMPEDANCE MATCHING

## **RGPC 1200 Custom**

## **Parallel Power Delivery**

The RGPC 1200 Custom (available in black or silver) with its beautiful award winning Art Deco design, switchable backlit logo (blue, orange or off), with Six Duplex outlets is perfect for the most demanding AV systems.

To receive the maximum performances install the RGPC 1200 Custom as close as possible to the AV equipment.

The RGPC 1200 Custom utilizes Balanced Surge Protection Design (SPD) to ensure Bidirectional Protection and Reduced Ground Interference.

SPECIFICATIONS	1200 CUSTOM 120/120	1200 CUSTOM 240/240
Dimensions (WHD)	17 x 5.25 (w/feet 6.2) x 11	17 x 5.25 (w/feet 6.2) x 11
Net weight	55 lbs	55 lbs
Mounting	Stand alone Floor / Shelf	Stand alone Floor / Shelf
Rack Mountable (w/ included detachable ears)	Yes	Yes
Power Cord (Detachable)	6 ft, 12 AWG, NEMA 5-15P	6 ft, 12 AWG, Euro Schuko Plug
Outlets	12 (NEMA 5-20R)	8 Euro Schuko
Input Voltage	120 VAC	240 VAC
Output Voltage	120 VAC	240 VAC
Frequency	60 HZ	50 HZ
Output Power	12 A (1,440 Watts)	12 A (2,880Watts)
Technology	Parallel Power Delivery	Parallel Power Delivery
AC Surge Protection (type 3 locations)	Balanced	Balanced
Efficiency	>99%	>99%
Cooling	Convectional	Convectional
Storage Temperature	-40° C to 85° C	-40° C to 85° C
Operating Temperature	-40° C to 65° C	-40° C to 65° C