

# Technical Specifications

<b>Tube Complement:</b>	2 x ECC83 (12AX7), 2 x 6H30
<b>Output power:</b>	150W + 150W RMS @ 8 Ohms 220W + 220W RMS @ 4 Ohms
<b>Frequency response:</b>	-1dB @ 12Hz & 45kHz, -3 dB @ 6Hz & 80 kHz
<b>Input impedance:</b>	24k Ohms / 100pF
<b>Input sensitivity:</b>	860mV RMS
<b>Input stage:</b>	Pure A class, double triode totem pole ECC83
<b>Driver stage:</b>	Pure A class, double triode totem pole 6H30
<b>Output stage:</b>	Class AB thermostable, complementary Hexfet
<b>Input:</b>	6 line (3 x RCA, 2 x XLR, 1 bypass RCA)
<b>Line Outputs:</b>	1 tape, 1 sub (volume controlled)
<b>Output connectors:</b>	4 + 4 bi-wiring
<b>THD:</b>	<0.15% @ 1kHz, 1W <0.25% @ 1kHz, 10W <0.35% @ 1kHz, 100W <0.9% @ 20Hz - 20kHz, 150W
<b>Output resistance:</b>	<0.4 Ohms
<b>Dimensions:</b>	H 7.1" x W 17.1" x D 17.3" (H 180mm x W 435mm x D 440mm)
<b>Net weight:</b>	55.1 lbs (25kg)