

Our commercial in-ceiling speakers are designed to look as good as they sound, with a modern, no-edge design and a sturdy, perforated steel grill that can be painted to match any ceiling color. Visitors to the venue, whether it's a church, restaurant, boardroom, or classroom, will barely notice the speakers — but they will appreciate the crystal clear sound.

Dealers will also appreciate the extra-wide threaded screws for quick dog leg fastening, the removable scrim cloth, and the neodymium magnets that securely attach the grill to the speaker enclosure, all resulting in fast and easy installation.

### KEY FEATURES

- Modern No Edge 2 Way In-Ceiling Design
- 70V/100V Transformer for Commercial Applications
- Tap Settings
  - 100V: 8Ω, 15W, 10W, 5W, 2.5W
  - 70V: 8Ω, 10W, 5W, 2.5W, 1.25W
- Dual Coated (Zinc and Powder) Steel Grill firmly attached with Neodymium Magnets
- Extra Wide Threaded Screws for Quick Dog Leg Fastening
- Large Push Terminals
- Removable Scrim Cloth
- Attractive No Edge Design
- LIFETIME WARRANTY



## FLC-600T

### ACOUSTIC SPECIFICATIONS

- 6.5" (165.1mm) Polypropylene Woofer
- 0.5" (12.7mm) PEI Tweeter
- 5/70 WPC Power handling
- 87db SPL
- Impedance 8ohm/70V/100V
- Frequency Response 52Hz - 20kHz

### MECHANICAL SPECIFICATIONS

- Baffle Diameter: 9.25" (235mm)
- Mounting Depth: 3.5" (89mm)
- Cut Out Dimensions: 8.25" (210mm)
- Pre-Construction: Use Vanguard PCBC-6

