



S C M 5 0 S L A T : 3 - w a y a c t i v e *

- Features**
- ATC SM-150 s Soft Dome Mid driver.
 - Latest 234mm SL Spec Bass driver.
 - Massive ATC motor assembly.
 - Wide dispersion and perfect imaging.
 - 350 watt Class A (to 2/3 max power) Tri-amplifier.
 - Active filters and overload protection.
 - 6 year warranty.
 - Any veneer to order. Featured veneer: Rosewood.

Specifications **Drivers** : HF 25mm Neodymium, Mid 75mm ATC Soft Dome, LF 243mm SL **Frequency Response (+/-2dB)** : 70Hz-17kHz **(+/-6dB)** : 38Hz-22kHz
Matched Response : +/-0.5dB **Dispersion** : ±80° Coherent Horizontal, ±10° Coherent Vertical **Max SPL** : 112dB **Crossover Frequencies** : 380Hz and 3.5kHz
Connectors : Male XLR **Filters** : All active **Amplifier Output** : 250w LF, 100w Mid, 50w HF
Cabinet Dimensions (HxWxD) : 1003x304x470mm **Weight** : 53.3kg

***Passive version also available :** **Sensitivity** : 85dB@1w@1 metre **Weight** : 41.5kg **Suitable for use with amplifiers of** : 100-1500w

ATC reserves the right to vary products and specifications without prior notice.

