

ALVA TT V2

Direct Drive Turntable with Bluetooth® aptX HD



Just Add Vinyl

You've spent years curating the perfect record collection, searching for hidden gems in record shops and online – because you love music. Our shared love means that we didn't stop with Alva TT.

We pushed on to create Alva TT V2; with a direct drive system, bespoke MC cartridge, an all-new tone-arm, and Hi-Res Bluetooth with an integrated phono stage – both now switchable.

We believe that your records deserve to sound as fantastic as they look.

Highlights

- **Bluetooth aptX HD** – Switchable Hi-Res wireless streaming. Place the turntable on a flat surface that suits you.
- **Built-In Phono Stage** – Switchable phono pre-amp, direct connection to amp – keep your setup simple.
- **Direct Drive** – Consistent drive speed with pitch-perfect audio reproduction.
- **Pre-installed High-Output MC Cartridge** – Pristine musical detail, custom design. Easy setup.
- **New Tonearm with Removable Headshell** – Lightweight and strong. Tracks your records flawlessly.

Specification

TYPE	Direct Drive
TURNTABLE SPEEDS	33.3, 45rpm
WOW & FLUTTER	<0.1%
TURNTABLE PLATTER	POM (Polyoxymethylene)
PLATTER DIAMETER	305mm
PLATTER WEIGHT	2.2kg
AUDIO OUT	RCA Phono/Line Level (Switchable)
BLUETOOTH	SBC/aptX/aptX HD
POWER SUPPLY	AC 100-240V, 60/50Hz
POWER CONSUMPTION	5.5W
MAX POWER CONSUMPTION	20W
STANDBY POWER CONSUMPTION	<0.25W
DIMENSIONS (W X H X D)	435 x 139 x 368mm
WEIGHT	10.9kg
PHONO STAGE GAIN @1KHZ	42dB
PHONO STAGE NOMINAL OUTPUT	250Vrms
PHONO STAGE INPUT NOISE (A-WEIGHTED)	0.1u Vrms
PHONO STAGE RIAA CURVE ACCURACY	*+/- 0.3dB 30Hz-20kHz
PHONO STAGE SIGNAL/NOISE RATIO	>90dB
PHONO STAGE THD+N 1KHZ	0.0025%
PHONO STAGE INPUT IMPEDANCE	47kΩ
PHONO STAGE INPUT CAPACITANCE	330pF
TO NEARM TYPE	Static Balanced Tonearm w/ detachable Headshell
TO NEARM EFFECTIVE LENGTH	221.5mm
TO NEARM OVERHANG	19mm
TO NEARM EFFECTIVE MASS	19.6g
TO NEARM COMPATIBLE CARTRIDGE WEIGHTS	4.5-12g
CARTRIDGE	High Output Moving Coil
CARTRIDGE FREQUENCY RESPONSE	*+/- 1dB 30Hz-20kHz
CARTRIDGE STYLUS	Elliptical
CARTRIDGE CANTILEVER	Aluminium
CARTRIDGE OUTPUT LEVEL	2mV @1kHz
CARTRIDGE TRACKING FORCE	2g
CARTRIDGE RECOMMENDED LOAD	47kΩ
IN THE BOX	ALVA TT V2 direct drive turntable, Dust cover, Quick start guide, 2 x hinge assembly, Ortofon stylus gauge, Counterweight, Removable headshell with moving-coil cartridge, POM platter assembly, Region specific mains leads, RCA cable, Safety guide, Ground lead.