

EWS Information

In-Wall & Center Speakers



SPECIFICATIONS:

	EWS530C	EWS600	EWS800
Power Handling Max	350 Watts	300 Watts	500 Watts
Frequency Response	40Hz-20kHz	40Hz-20kHz	30Hz-20kHz
Nominal Impedance	8-Ohm	8-Ohm	8-Ohm

DIMENSIONS:

	EWS530C	EWS600	EWS800
Outer Dim.	13 3/4" x 9 3/4" (349mm x 248mm)	11 15/16" x 8 9/16" (303mm x 248mm)	13 3/4" x 9 3/4" (349mm x 248mm)
Cut Out Dim.	12 7/8" x 8 13/16" (326mm x 224mm)	10 7/8" x 7 7/16" (275mm x 188mm)	12 7/8" x 8 13/16" (326mm x 224mm)
Mounting Depth	3 3/16" (85mm)	3 9/16" (90mm)	4 1/16" (103mm)

INTENDED USE:

- Architects custom projects / high-end designs
- Contractors, custom installers and retailers
- Kitchens, hall-ways, bathrooms, atriums
- Home theater & 2-channel/music systems
- New construction & retrofit applications



Earthquake Sound Corporation
 2727 McCone Avenue, Hayward, CA 94545 • Phone: 510.732.1000 • Fax: 510.732.1095
www.earthquakesound.com