

**UK** +44 (0) 1438 833577 **US** +1 (603) 742 9181 www.**FUTUREAUTOMATION**.NET



SPECIFICATION	MEASUREMENTS		
Screen Sizes (Approx)	19" - 32"		
Maximum Weight Capacity	25Kg (55lb)		
Maximum Weight Capacity (Marine)	16Kg (35lb)		
Maximum Screen Height	410mm (16.14")		
Packaging Dimensions	920mm (36.2") x 550mm (21.7") x 250mm (9.8")		
Shipping Weight	15Kg (33lb)		
Movement Type	Motorised		
Power Supply Required	110V or 240V AC		
Power Consumption	250-500W		
Power Consumption Standby	3W		
Decibel Rating	58dB		
Mounting Patterns Supported	VESA 200 W x 300, 200 H		
Control Options	IR Remote, RS232, Contact Closure		
Product Options / Features	Specific B&O and Loewe mounts / adapters, Custom RAL paint finishes, Outdoor version		
Package Contents	Mechanism, IR remote control		
Marine Suitable	Yes (Indoor)		



### **CABLE ROUTING**

Screen cables are routed behind the Base Panel and out the right side of the Beam into the Cable Track. Cables must be routed carefully to prevent any interference with the LSL beam as it operates.

Screen and Mechanism cables should be routed to a control box in the bottom of the cabinet.







### future automation fal

**TECHNICAL SHEET ISSUE 005** SHEET 3



UK +44 (0) 1438 833577 US +1 (603) 742 9181 www.FUTUREAUTOMATION.NET

### fa future automation



#### DETAIL D SCALE 1 : 3







### future automation

Shown with a tapered Box Enclosure



### **BASE PANEL & ENCLOSURE LID DETAILS**

NOTE: A tapered Box Enclosure Lid creates a good fit in the Cabinet Aperture and helps the Box Enclosure to locate within the Cabinet.





**UK** +44 (0) 1438 833577 **US** +1 (603) 742 9181 www.**FUTUREAUTOMATION**.NET





### OVERALL MECHANISM DIMENSIONS

**MECHANISM UP** 



**UK** +44 (0) 1438 833577 **US** +1 (603) 742 9181 www.**FUTUREAUTOMATION**.NET

