



HYPERION

The truest testament to the quality and performance of any audio component is what others in that industry have to say about it.

The **HYPERION** is the cartridge of choice for the most esteemed audio equipment manufacturers. Why? Because when they exhibit their gear at HiFi shows, they want their turntable, amplifier or speaker systems to sound the very best that they can! Peter Ledermann's radical design utilizes an actual "cactus spine" for the cantilever. The naturally tapered shape, stacked columnar fibers and

desiccated resin damping fit the exact parameters of the perfect cantilever: Low mass, extreme rigidity, internal damping, and tremendous strength. Also available in a Dual Compliance Design for older Linear Tracking turntables as the HYPERION LT. HYPERIONS are offered with a choice of CL or OC-CL styli

HYPERION / HELIOS Technical specifications

Stylus: Contact Line Nude, 0.100mm SQ	(stereo only): 1000 Hz >36 dB (LT: > 34dB) 50-15,000 >25 dB
Radius of curvature	
Selected Diamond shapes: CL or Optimized (OCL)	Channel difference: <0.5 dB (Stereo) <1.0 dB (Mono)
Cantilever: Hand formed/ treated selected Cactus „Spine“	Output voltage HYPERION: 0.4 mV
Recommended Tracking force: 1.8 to 2.2 Grams	Output voltage HELIOS: 1.1 mV
Effective tip mass: 0.30 mg	Cartridge weight: 10.25 Grams
Compliance: 10µm/mN (low compliance) (LT) 12µm/mN vertical 7µm/mN horizontal	Loading HYPERION: ≥ 470 Ω
Frequency response: 20-20,000 Hz ± 1.0 dB	Loading HELIOS: ≥ 1.5 kΩ
Channel Separation	



HELIOS

This is our new medium output design. All other technical specifications are identical to the HYPERION