



# UPS-1440-Li-ISO

## TECHNICAL DESCRIPTION

The UPS-1440-Li-ISO shall be a two-rack-space or tower line interactive UPS unit in a steel and plastic enclosure. It shall operate at 120 volts AC at both 50 or 60Hz and have a 6-foot, grounded, 3-wire #14 line cord. There shall be 8 grounded AC receptacles on the back panel. This unit can accommodate additional battery cabinets to extend its autonomous run time. Overall dimensions shall be 20.7" D x 17.25" W x 3.39" H. Weight shall be 77 pounds. The UPS-1440-Li-ISO shall have a total load rating of 1440VA / 1296 Watts. This unit can accommodate an optional SNMP network card for unit monitoring and shutdown.

SPECIFICATIONS	UPS-1440-Li-ISO
Load Rating	12A In 12.0A / 10.8A Out
Voltage Rating	120V
Power Requirement (no load)	0
Input/Mains Plug Type	5-20P
Input/Mains Cord Length	6'
# of Receptacles	8
Receptacle Type	(8) 5-20R
Under-Voltage Auto Shutdown	Yes
Over-Voltage Auto Shutdown	Yes
Over-Current Auto Shutdown	Circuit Breaker
Network Port	Optional SNMP Card
Serial Port	RS-232 on Female 9-pin D-subminiature USB Type B RJ45 on optional SNMP card
Temperature Sensor Input	None
BTU/h Max	385 BTU/h
Auxiliary Relay Outputs	With optional relay card
Contact Closure Input	Optional relay card
Dimensions	20.7" x 17.25" x 3.39"
Weight	77 lbs
Temperature Range:	0C to 40C
Humidity Range	5% to 95% R.H. Non-condensing
Agency Listings	UL 1778 5th Edition CSA-C22.2 Nos. 107.3-14

\* 1.2 x 50 microsecond industry standard combination wave surge as per IEEE C62.41

\*\* Specifications subject to change without notice

Specifications Version: ESP-SRX\_Product\_Specs\_Master 03.05.21.xlsx

