
### Detailed Specifications & Technical Data



## **CABLE-2A**





#### **Description**

Bulk cable used to make Series 2 audio cables	
Features	
Twisted Pair Audio pair Siamese extruded cable construction	
24AWG solid Oxygen Free Copper conductors	
100% shielded with Aluminum Mylar wrap to lower noise floor	
Highly flexible PVC jacket	
Available in 328 foot spools or shorter custom lengths	
Conductor	
Construction	Solid 24AWG
Material	Oxygen Free Copper OFC
Insulation	
Insulation Material	Foam PE –Polyethylene (Red & White)
Thickness	2.3mm
Shielding	
Aluminum Mylar	100% shield
Outer Jacket	
Material	Black PVC – Polyvinyl Chloride
Outside Diameter	5.5 + 5.5mm

#### Notes

While Tributaries has made every reasonable effort to ensure the accuracy of these specifications, information contained herein may be subject to error and omission and to change without notice. Tributaries provides these specifications on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied.

The cable will be packaged to preclude the inducement of damage due to handling and transportation, and will be in accordance with the best commercial practices available. Shipping containers will be constructed as to eliminate any possible damage to the cable due to shipment.

Net Weight: 20 lbs. / 300 ft. spool



# **CABLE-2A**

**Put-Ups and Colors** 

Stock Code	Description	Color	Put-Up
CABLE-2A	Series 2 Audio Cable	Black	328 ft. spool