

## PWRS-T8



### Description

8 outlet surge suppressor power strip

### Attributes

- All outlets 3-line AC power protected
- 2 Regular surge protected outlets with safety shutters
- 6 180° rotating outlets can be rotated to different direction for plug management
- Power push button integrates a 15 Amp overload re-settable circuit breaker
- Protected Indicator: red light indicates that the AC surge protection is operating properly
- Grounded Indicator: blue light indicates your electrical wiring is properly grounded
- Cord management design to avoid a jumbled mass
- 3-year parts & labor warranty
- \$25,000 connected equipment warranty

### Specifications

|                            |                                      |   |
|----------------------------|--------------------------------------|---|
| Electrical Rating          | <b>15A, 125VAC, 60Hz, 1875 Watts</b> |   |
| Surge Joule Rating         | <b>2160J</b>                         |   |
| Surge Protection Mode      | <b>L-N, L-G, N-G</b>                 |   |
| UL Clamping Voltage        | <b>400V</b>                          |   |
| Maximum Peak Spike Current | <b>19,200 A</b>                      |   |
| Maximum Spike Voltage      | <b>6KV</b>                           |   |
| EMI/RFI Noise Filter       | Frequency                            | <b>150KHz – 100MHz</b>                  |
|                            | Attenuation                          | <b>Up to 58dB</b>                       |
| Network Line Protection    | Jack Type                            | <b>RJ45 / 8P8C (1 in – 1 out) Combo</b> |
|                            | Protection Speed                     | <b>1,2,3,6</b>                          |
|                            | Communication Speed                  | <b>10/100 Base-T (CAT5)</b>             |

## PWRS-T8

|                              |                 |  |
|------------------------------|-----------------|--|
| DSS / COAX Cable Protection  | Surge Arrestor  | <b>Gas Tube</b>  |
|                              | Breakdown Volts | <b>&lt; 75V</b>  |
|                              | Insertion Loss  | <b>&lt; 0.1dB</b>  |
|                              | Line Protection | <b>1 Line</b>  |
| Surge Protected Indicator    |                 | <b>Blue LED</b>  |
| Ground O.K. Indicator        |                 | <b>Blue LED</b>  |
| Surge Protected Failure      |                 | <b>Surge Circuit Shut Down &amp; Auto Power Shut Down</b>    |
| Accessories                  |                 | <b>1 – Coax cable, Mounting hardware</b>                     |
| Safety Approval & Compliance |                 | <b>UL1363, UL1449, UL498A, UL497A, UL1283, UL452, UL1492</b> |

### Notes

While Tributaries® has made every reasonable effort to ensure the accuracy of these specifications, information contained herein may be subject to error and omission and to change without notice. Tributaries provides these specifications on an “AS IS” basis, with no representations or warranties, whether express, statutory or implied.

Net Weight: 2.18 lbs.

### Put-Ups

| Stock Code | Description                           | Color | Quantity          |
|------------|---------------------------------------|-------|-------------------|
| PWRS-T8    | 8 Outlet Surge Suppressor Power Strip | N/A   | Each              |
| PWRS-T8M   | 8 Outlet Surge Suppressor Power Strip | N/A   | Master Pack of 10 |