

SPECIFICATIONS

Specifications are subject to change without notice.

Model	Impact X 10"	Impact X 12"
Driver	10" forward firing	12" forward firing
Amplifier Class A-B	600 watts Dynamic 300 watts RMS	800 watts Dynamic 350 watts RMS
Frequency Response: Overall Frequency Response: (+/- 3dB)	32-180 Hz	29-180 Hz
Frequency Response: Overall Frequency Response: (+/- 10dB)	25-250 Hz	23-250 Hz
Low-Pass Crossover	50 - 200 Hz (12dB/ Octave)	50 - 200 Hz (12dB/ Octave)
Phase	0° to 180°	0° to 180°
Cabinet Design	20mm MDF	20mm MDF
Magnet Structure	Dual ferrite magnet motor	Dual ferrite magnet motor
Woofers	10" high excursion double vented basket driver with reinforced paper membrane	12" high excursion double vented basket driver with reinforced paper membrane
Voice Coil	Four Layer 2" / 52mm voice coil	Four Layer 2" / 52mm voice coil
Input	gold plated stereo /LFE RCA, nickel plated high level in	gold plated stereo /LFE RCA, nickel plated high level in
Output	gold plated stereo /LFE RCA,	gold plated stereo /LFE RCA,
Power selector	Off / Auto / ON	Off / Auto / ON
Finishes	Black / White	Black / White
Dimensions (W/H/D) incl. feets + connectors	32cm x 36cm x 40 cm	36cm x 42cm x 51 cm
Weight (approx.)	15kg	18kg
Shipping weight (approx.)	17kg	20kg